



Naturelite SolaGlaze Solid Polycarbonate Roofing

An outstanding class of polycarbonate roofing sheets combining superior impact resistance, elegant smooth appeal, flexibility, excellent light transmission properties and UV protection. Naturelite's SolaGlaze solid polycarbonate sheets are chosen by architects, building professionals and renovators for its high quality physical properties, ease of installation and as an attractive, practical alternative to glass.

Main Features & Advantages

- Protection from harmful UV rays.
- High impact strength-approx.250 times stronger than glass.
- Excellent light transmission properties.
- Lightweight and easy to install.
- Sturdy construction.
- Suitable for high wind areas.
- Excellent weather and watertightness when installed properly.
- Flexible and versatile - can be cold curved on site.
- Fire resistant properties.
- Low maintenance.
- Suitable for exterior and internal applications.
- 10 year warranty against hail damage for
- Hail stones measuring up to 25mm in diameter.
- Complementing range of extrusions and installation Accessories designed to maximise ease and efficiency of installation.



Common Applications

Pergolas, patios, courtyards, balconies, shopping centres, skylights and sidelights, residential and commercial roofing projects, shelters, building architectural projects, walkways, carports, privacy screens.

Tel : (02) 9750 7128

Fax : (02) 9750 7031

Web: www.naturelite.com.au

Add : 61 Lakemba St. Belmore

Email : info@naturelite.com.au

Web: www.KBMS.com.au

SolaGlaze Available SIZE

Lengths Available:


Minimum 1.0 metres up to 10 metres. Other lengths available on request. Apply double sided tape to supporting rafters (mid rafters).

Contact your Naturelite product rep for advice on installing SolaGlaze® sheets on purlins/ battens, curved structures and high wind loads.

Other colours and lengths available on request. Also available in 6mm thickness.




SolaGlaze Available Color



CLEAR

maximum light transmission with the benefits of uv protection and high impact resistance. Popular as a substitute for glsss.


Light Transmission:89%
Heat Transmission:87%



GREY

Pleasant diffused lighting with a grey tint,provides excellent shade cover.


Light Transmission:66%
Heat Transmission:64%



BRONZE

Pleasant diffused lighting with a bronze tint,provides excellent shade cover.Light

Transmission:50%
Heat Transmission:48%



OPAL(white)

Excellent clarity,comfortable diffused lighting effect.

Light Transmission:20%
Heat Transmission:18%



SolaGlaze Extrusions

50mm Aluminium H Bar with rubber gaskets

Available Color in: Dark Grey, Silver Grey, White, Primrose.

Other available accessories : H-bar ,end caps, screws for timber and metal fixings.

For care and installation with advice, please refer to the Naturelite SolaGlaze® Solid Polycarbonate Roofing Sheets - Care and Installation Advice Brochure. Advice on high wind loads and radii for curved structures can be obtained from your Naturelite product rep.

Tel : (02) 9750 7128

Fax : (02) 9750 7031

Web: www.naturelite.com.au

Add : 61 Lakemba St. Belmore

Email : info@naturelite.com.au

Web: www.KBMS.com.au